

Manage threat collections

Published: 2025-04-28

ExtraHop RevealX can apply [threat intelligence](#) to your network activity based on threat collections provided by ExtraHop, CrowdStrike, or other free and commercial sources.


Before you begin

- Learn about [threat intelligence](#).
- You must have [System and Access Administration privileges](#) on each console and sensor to manage threat collections.
- If your ExtraHop deployment includes a console, we recommend that you [transfer management](#) of all connected sensors to the console to enable or disable built-in threat collections across your entire system.

Enable or Disable built-in threat collections

Built-in threat collections from ExtraHop and CrowdStrike identify indicators of compromise throughout the system.

Enabled threat collections automatically update systems that are connected to ExtraHop Cloud Services. You can confirm connectivity on the [ExtraHop Cloud Services](#) page in the Administration settings.

1. Log in to the ExtraHop system through `https://<extrahop-hostname-or-IP-address>`.
2. Click the System Settings icon  and then click **Threat Intelligence**.
3. In the Built-In Threat Collections table, click **Enable** or **Disable** in the Actions column.

The system automatically checks for updates to ExtraHop and CrowdStrike threat collections every 6 hours.

Built-In Threat Collections			
Built-in threat intelligence collections are available by default on your Reveal(x) system. This console manages shared settings for 3 of 3 connected sensors.			
Name	Status	Actions	
CrowdStrike Falcon: Hostnames and URIs	Enabled	Disable	
CrowdStrike Falcon: IP Addresses	Enabled	Disable	
Malicious Botnet Host Names and URIs	Enabled	Disable	
Malicious Botnet IP Addresses	Enabled	Disable	
Malicious Brute Force IP Addresses	Enabled	Disable	
Malicious C2 IP Addresses	Enabled	Disable	
Malicious Cobalt Strike C2 IP Addresses	Enabled	Disable	
Malicious Host Names and URIs (I)	Enabled	Disable	
Malicious Host Names and URIs (II)	Enabled	Disable	
Malicious IP Addresses	Enabled	Disable	


Upload a threat collection

Upload threat collections from free and commercial sources to identify indicators of compromise throughout the ExtraHop system. Because threat intelligence data is updated frequently (sometimes daily), you might need to update a threat collection with the latest data. When you update a threat collection with new data, the collection is deleted and replaced, and not appended to an existing collection.

 **Important:** STIX 1.0 file uploads are now deprecated and will be removed in a future release.

You must upload threat collections individually to your console, and to all connected sensors.

Here are some considerations about uploading threat collections.


- Custom threat collections must be formatted in Structured Threat Information eXpression (STIX) as compressed TAR files, such as .TGZ or TAR.GZ. RevealX currently supports uploads of STIX file versions 1.0 - 1.2.
 - The maximum number of observables that a threat collection can contain depends on your sensor memory and license. To ensure successful uploads within the limits of your sensors and license, we recommend breaking collections into files of less than 3,000 observables, with a total collection size of less than 1 million observables. Contact your ExtraHop representative for more information about license and platform limits for uploading threat collections.
 - You can [upload STIX files through the REST API](#).
1. Log in to the ExtraHop system through `https://<extrahop-hostname-or-IP-address>`.
 2. Click the System Settings icon  and then click **Threat Intelligence**.
 3. Click **Manage custom collections**.
 4. Click **Upload New Collection**.
 5. In the Collection ID field, type a unique collection ID. The ID can only contain alphanumeric characters and spaces are not allowed.
 6. Click **Choose file** and select a .tgz file that contains a STIX file.
 7. Type a display name in the Display Name field.
 8. Click **Upload Collection**.
 9. Repeat these steps on all consoles and each connected sensor.

Add a TAXII feed

Threat collections can be delivered to your environment over the Trusted Automated Exchange of Intelligence Information (TAXII) protocol.

TAXII feeds can vary in quality or relevance to your environment. To maintain accuracy and reduce noise, we recommend that you only add feeds from reliable sources that provide high-quality threat intelligence data.

Before you begin

- TAXII feed indicators are processed by ExtraHop Cloud Services. The ExtraHop system must be [connected to ExtraHop Cloud Services](#) to add a TAXII feed.
 - TAXII feeds can only be managed from a console by users with NDR module access and administration [privileges](#).
 - TAXII feed indicators are only delivered to connected sensors running firmware versions 9.6.0 and later.
 - RevealX currently supports TAXII feeds for TAXII versions 2.0 - 2.1 that contain STIX file versions 2.0 - 2.1
 - You can only configure one TAXII feed for the ExtraHop system.
1. Log in to the ExtraHop system through `https://<extrahop-hostname-or-IP-address>`.
 2. Click the System Settings icon  and then click **Threat Intelligence**.
 3. In the TAXII feed section, click **Add TAXII Feed**.
 4. In the Name field, type a unique name for the TAXII feed.
 5. In the TAXII Server Discovery URL field, type the discovery URL for your TAXII feed provider.
 6. From the TAXII version drop-down menu, select the TAXII protocol version of the feed.

7. Select an authentication type.

- No authentication
- Basic authentication

Enter the username and password for the target feed.

8. Specify a certificate for the target feed.

- No certificate
- CA certificate

The certificate presented by the TAXII server will be verified against this certificate. Copy and paste the root Certificate Authority (CA) certificate.

9. Click **Test Connection** to confirm URL, authentication, and certificate settings.

10. Click **Next**.

11. From the Collections for Enrichment drop-down menu, select the threat collections that will result in a suspicious tag when an indicator match occurs.

12. From the Collections for Detection Creation drop-down menu, select the threat collections that will result in a detection when an indicator match occurs.



Note: You can assign a collection to both enrichment and detection creation. If a collection is not assigned to the enrichment option, the collection will not be updated during polling and indicators from the collection will not appear in your system.

13. In the Maximum Lookback field, type the number of days in the past you want to accept indicators from the threat collection.

You can set this value to a number between 1 and 15 days. The feed will only accept indicators that were created during this lookback period.

14. In the Polling Frequency field, type the number of hours between polling the TAXII feed for threat collection updates.

You can set this value to a number between 1 and 24 hours.

15. Click **Save**.

TAXII feed configuration information displays in the TAXII Feed section of the Threat Intelligence page, including the specified lookback period, polling frequency, and total number of indicators contained in the feed. The TAXII Collections table contains details about the individual collections in the feed.

TAXII Feed
Add a TAXII feed to provide an up-to-date stream of threat indicators.

Name: ExampleFeed 1
TAXII Server Discovery URL: https://example.taxii.feed.com/
Collections: Brute Force List, VulnFeed, Cyberscout Analysis
Maximum Lookback: 15 days
Polling Frequency: 6 hours
Indicators: 10,136
[Edit](#) [Remove](#)

TAXII Collections

TAXII Feed	Collection	Imported Indicators	Match Result	Status	Last Polled
ExampleFeed 1	Brute Force List	4,326	Detection Enrichment and Creation	Up-to-date	2024-03-22 12:41:58
ExampleFeed 1	Cyberscout Analysis	2,902	Detection Enrichment	Up-to-date	2024-03-22 12:41:01
ExampleFeed 1	VulnFeed	-	Detection Enrichment	-	2024-03-22 12:45:34

Annotations:

- Feed configuration information:** Points to the configuration fields above the table.
- Total indicators imported:** Points to the 'Indicators: 10,136' field.
- Collection details:** Points to the 'TAXII Collections' table.
- Indicators imported by collection:** Points to the 'Imported Indicators' column.
- Poll status unavailable:** Points to the 'Status' column for the 'VulnFeed' row.
- Indicator matches are tagged and generate a detection:** Points to the 'Match Result' column for the 'Brute Force List' row.
- Indicator matches do not generate a detection:** Points to the 'Match Result' column for the 'Cyberscout Analysis' row.

Here are some considerations about TAXII feeds:

- TAXII feed polling is limited to 25,000 indicators across all collections.
- Indicator types that are not recognized by the ExtraHop system, benign endpoint indicators, and indicators marked as revoked will be removed from the feed during polling.
- In the TAXII collections table, the collection status will display a dash (-) until the collection is up-to-date. If this status does not resolve to up-to-date, test your connection to the TAXII server, then check your TAXII feed provider to make sure that the collection still exists in the feed, that your credentials grant access to the collection, and that you have not exceeded polling limits set by the provider. A partial update status will display if a collection does not fully update during polling. Partial updates can occur if the polling was interrupted unexpectedly or if a provider rate limit was reached.