

Assign an alert configuration to a source

Published: 2018-04-20

Although you configure alert settings from the System Settings window, you assign an alert configuration to a source from the Metrics page in the ExtraHop Web UI. You must assign an alert to a source before it can monitor your environment.

Before you begin

You must configure an alert before it can be assigned. See [Configure threshold alert settings](#), [Configure trend alert settings](#), or [Configure Addy anomaly alert settings](#).

For threshold and trend alerts, you can only assign the alert configuration to the same source type as the monitored metric.

For anomaly alerts, you can only assign the alert configuration to the same source type you selected in the alert settings.

The following procedure shows you how to assign an alert configuration to a device, which is similar for assigning alert configurations to applications and device groups.

1. Log into the Web UI on the ExtraHop Discover or Command appliance.
2. Click **Metrics** from the top menu.
3. Click **Devices** in the left pane.
4. Select the checkbox for each device you want monitored by the alert configuration.
5. Click the **Assign Alert** icon from the top of the page.
6. Select the checkbox for each alert configuration you want to assign to the selected devices.
7. Click **Assign Alerts**.

The alert configuration monitors the selected devices for the alert conditions specified in the alert settings.



Tip: You can also manage alert assignments for a device, device group, or application from the Overview page for that source. From the Manage... section, click **Assignments** or **Alerts** to add or remove alert assignments from the source and to view which alerts are already assigned to the source.

Next steps

- View generated alerts in the [Alert History](#)