

# Configure a MongoDB target for an open data stream

---

Published: 2018-10-09

You can export data on an ExtraHop Discover appliance to any system that receives MongoDB input for long-term archiving and comparison with other sources.

1. Log into the Admin UI on the ExtraHop Discover appliance.
2. In the System Configuration section, click **Open Data Streams**.
3. Click **Add Target**.
4. From the Target Type drop-down menu, select **MongoDB**.
5. In the Name field, type a name to identify the target.
6. In the Host field, type the hostname or IP address of the remote MongoDB server.
7. In the Port field, type the port number of the remote MongoDB server.
8. Select **SSL/TLS Encryption** to encrypt transmitted data.
9. Select **Skip certificate verification** to bypass certificate verification of encrypted data.
10. Optional: Add users that have permission to write to a MongoDB database on the target server.
  - a) In the Database field, type the name of the MongoDB database.
  - b) In the Username field, type the username of the user.
  - c) In the Password field, type the password of the user.
  - d) Click the plus (+) icon.
11. Optional: Click **Test** to establish a connection between the Discover appliance and the remote MongoDB server and send a test message to the server.

The dialog box displays a message that indicates whether the connection succeeded or failed. If the test fails, edit the target configuration and test the connection again.
12. Click **Save**.

## Next steps

Create a trigger that specifies what MongoDB message data to send and initiates the transmission of data to the target. For more information, see the [Remote.MongoDB](#) class in the [ExtraHop Trigger API Reference](#).