

# Discover and Command Post-deployment Checklist

---

Published: 2018-10-09

After you deploy the ExtraHop Discover or Command appliance, log into the Admin UI and configure the following settings.

## Password

Maintain system security after the evaluation period. Change the default password. For more information, see the [Default User Accounts FAQ](#).

## NTP

Time is critical in the ExtraHop appliance, particularly when doing event correlation with time-based metrics and logs. Verify that the NTP settings are correct for your infrastructure, test settings, and sync NTP. For more information, see [Configure the system time](#).

## Time Zone

The correct time zone is critical to run scheduled reports at the correct time. Ensure the ExtraHop appliance has the correct time zone. For more information, see [Configure the system time](#).

## Remote Authentication

Set up remote authentication. The ExtraHop appliance integrates with RADIUS, TACACS, and LDAP for remote integration. For more information, see the [Remote Authentication](#) section in the Admin UI guide.

## Firmware Update

The ExtraHop appliance firmware is updated often with enhancements and resolved defects. Verify that you have the current firmware. For more information, see [Upgrade the firmware on your ExtraHop appliance](#).

## Audit Logging

The ExtraHop appliance can send events to a remote syslog collector. For more information, see the [Send audit log data to a remote syslog server](#).

## SMTP

The ExtraHop appliance can email alerts and system-health notifications. Set up and test notifications. For more information, see [Configure email settings for notifications](#).

## System Notifications

The ExtraHop appliance can send email when it detects problems. Create an email group to receive notifications. For more information, see [Configure an email notification group](#).

## iDRAC

Each physical ExtraHop appliance has an iDRAC port, similar to iLO or KVM over Ethernet. Connect and configure the iDRAC port. For more information, see [Configure the iDRAC Remote Access Console](#).

## SSL Certificate

Each ExtraHop appliance ships with a self-signed certificate. If you have a PKI deployment, generate your own certificate and upload it to each ExtraHop appliance. For more information, see the [SSL certificates](#) section in the Admin UI Guide.

## DNS A Record

It is easier to access an ExtraHop appliance by hostname than by IP address. Create an A record in your DNS root ("exa.yourdomain.local") for each ExtraHop appliance in your deployment. Refer to your DNS administration manual.

## Customizations and Datastore Backup

Create a system backup prior to upgrading firmware, or before making a major change in your environment. For more information, see [Back up a Discover or Command appliance](#).