

# Explore Post-deployment Checklist

---

Published: 2020-02-21

After you deploy the ExtraHop Explore appliance, log into the Explore Admin UI, and configure the following settings.

## Password

Maintain system security after the evaluation period. Change the default password. For more information, see the [Default User Accounts FAQ](#).

## NTP

Time is critical in the ExtraHop appliance, particularly when doing event correlation with time-based metrics and logs. Verify that the NTP settings are correct for your infrastructure, test settings, and sync NTP. For more information, see [Configure the system time](#).

## Time Zone

The correct time zone is critical to run scheduled reports at the correct time. Ensure the ExtraHop appliance has the correct time zone. For more information, see [Configure the system time](#).

## Remote Authentication

Set up remote authentication. The ExtraHop appliance integrates with [LDAP](#), [RADIUS](#), and [TACACS+](#) for remote integration.

## Firmware Update

The ExtraHop appliance firmware is updated often with enhancements and resolved defects. Verify that you have the current firmware. For more information, see [Upgrade the firmware on your ExtraHop appliance](#).

## Audit Logging

The ExtraHop appliance can send events to a remote syslog collector. For more information, see the [Send audit log data to a remote syslog server](#).

## SMTP

The ExtraHop appliance can email alerts and system-health notifications. Set up and test notifications. For more information, see [Configure email settings for notifications](#).

## System Notifications

The Explore appliance can send email notifications if disk errors are detected. Add email addresses to receive system health notifications. For more information, see the [Notifications](#) section.

## iDRAC

Each physical ExtraHop appliance has an iDRAC port, similar to iLO or KVM over Ethernet. Connect and configure the iDRAC port. For more information, see [Configure the iDRAC Remote Access Console](#).

## SSL Certificate

Each ExtraHop appliance ships with a self-signed certificate. If you have a PKI deployment, generate your own certificate and upload it to each ExtraHop appliance. For more information, see the [SSL certificate](#) section in the Admin UI guide.

## DNS A Record

It is easier to access an Explore appliance by hostname than by IP address. Create an **A** record in your DNS root ("**exa.yourdomain.local**") for each Explore appliance in your deployment. Refer to your DNS administration manual.