


Deploy the ExtraHop Command Appliance on a Linux KVM

Published: 2018-11-09

This document provides information on how to install the ExtraHop Command virtual appliance on a Linux kernel-based virtual machine (KVM). This guide assumes that you are familiar with basic KVM administration.

If you have not already done so, download the ExtraHop Command virtual appliance file for KVM from the [ExtraHop Customer Portal](#).

 **Important:** If you want to deploy more than one ExtraHop virtual appliance, create the new instance with the original deployment package or clone an existing instance that has never been started.

Requirements

Before you can install the ExtraHop virtual appliance, make sure that your environment meets the following requirements:

- A KVM hypervisor environment capable of hosting a VM that has:
 - 4 GB RAM
 - Two vCPUs
 - One 4 GB boot disk (virtio-scsi interface recommended)
 - One 40 GB datastore disk (virtio-scsi interface recommended)
- An ExtraHop virtual appliance license key

Package contents

The installation package for KVM systems is a `tar.gz` file that contains the following items:

ECA_KVM.xml

The domain XML configuration file

extrahop-boot.qcow2

The boot disk

extrahop-data.qcow2

The datastore disk

Determine the best bridge configuration

Identify the bridge through which you will access the management interface of your Command appliance.

1. Make sure the management bridge is accessible to the ExtraHop virtual appliance and to all users who must access the management interface.
2. If you need to access the management interface from an external computer, configure a physical interface on the virtual management bridge.
3. (Recommended) Configure separate bridges for the Command appliance management bridge and any bridge you will capture network traffic through on other ExtraHop appliances.

Edit the domain XML configuration file

After you identify the management bridge, edit the configuration file, and create the ExtraHop virtual appliance.

1. Extract the `tar.gz` file that contains the installation package.
2. Copy the two disks `extrahop-boot.qcow2` and `extrahop-data.qcow2` to your KVM system. Make a note of the location where you store these files.
3. Open the domain XML configuration file. Find and edit the following values:
 - a) Change the VM name (`ExtraHop-ECA`) to the name you want to assign to your ExtraHop virtual appliance.

```
<name>ExtraHop-ECA</name>
```

- b) Change the source file path `[PATH_TO_STORAGE]` with the location where you stored the virtual disk files in step 1.

```
<source file='[PATH_TO_STORAGE]/extrahop-boot.qcow2' />
<source file='[PATH_TO_STORAGE]/extrahop-data.qcow2' />
```

- c) Change the source bridge for the management network (`ovsbr0`) to match the name of your management bridge.

```
<interface type='bridge'>
  <source bridge='ovsbr0' />
  <model type='virtio' />
  <alias name='net0' />
  <address type='pci' domain='0x0000' bus='0x00' slot='0x03'
    function='0x0' />
</interface>
```

If you are configuring Open vSwitch virtual switch software for your virtual bridge, add the following `virtualport` type setting to the interface (after the source bridge setting):

```
<virtualport type='openvswitch'>
</virtualport>
```

4. Save the XML file.
5. Log in to the KVM console.
6. Create the new ExtraHop virtual appliance with your revised domain XML configuration file by running the following command:

```
virsh define ECA_KVM.xml
```

7. Start the virtual machine by running the following command:

```
virsh start <vm_name>
```

Where `<vm_name>` is the name of your virtual appliance.

Configure a static IP address

By default, ExtraHop appliances ship with DHCP enabled. If your network does not support DHCP, you must configure a static address manually.

1. Log into the KVM host.

2. Run the following command to connect to the ExtraHop appliance through the virtual serial console:

```
virsh console <vm_name>
```

Where `<vm_name>` is the name of your virtual machine.

3. Press ENTER twice to get to the appliance login prompt.

```
ExtraHop Discover Appliance Version 6.2.6.3385
IP: 192.0.2.81
exampleium login:
```

4. At the login prompt, type `shell`, and then press ENTER.
5. At the password prompt, type `default`, and then press ENTER.
6. To configure the static IP address, run the following commands:

- a) Enable privileged commands:

```
enable
```

- b) At the password prompt, type `default`, and then press ENTER.
- c) Enter configuration mode:

```
configure
```

- d) Enter the interface configuration mode:

```
interface
```

- e) Run the `ip` command and specify the IP address and DNS settings in the following format: `ip ipaddr <ip_address> <netmask> <gateway> <dns_server>`

For example:

```
ip ipaddr 10.10.2.14 255.255.0.0 10.10.1.253 10.10.1.254
```

- f) Leave the interface configuration section:

```
exit
```

- g) Save the running config file:

```
running_config save
```

- h) Type `y` and then press ENTER.

Post-deployment actions

After you configure an IP address for the Command appliance, log into the appliance with the following URL: `https://<command_ip_address>`. You will be prompted to accept a EULA and enter the product key to license the appliance.



Note: Log into the Web UI with the `setup` user account and type `default` for the password.

- Review the [Discover and Command Post-deployment Checklist](#) and configure additional Command settings.
- Connect the Command appliance to your Discover appliances.