

# Send audit log data to a remote syslog server

Published: 2020-02-23

The ExtraHop appliance audit log provides 90 days of lookback data about the operations of the system, broken down by component. You can view the audit log entries in the Admin UI or you can send the audit log events to a syslog server for long-term storage, monitoring, and advanced analysis. All logged events are listed in the Audit log events table below.

The following steps show you how to configure the ExtraHop appliance to send audit log data to a remote syslog server.

1. Log into the Admin UI on the ExtraHop appliance.
2. In the Status and Diagnostics section, click **Audit Log**.
3. Click **Configure Syslog Settings**.
4. In the Destination field, type the IP address of the remote syslog server.
5. From the Protocol drop-down menu, select **TCP** or **UDP**. This option specifies the protocol over which the information is sent to your remote syslog server.
6. In the Port field, type the port number for your remote syslog server. By default, this value is set to 514.
7. Click **Test Settings** to verify that your syslog settings are correct. If the settings are correct, you should see an entry in the syslog log file on the syslog server similar to the following:

```
Jul 27 21:54:56 extrahop name="ExtraHop Test" event_id=1
```

8. Click **Save**.

## Next steps

After you confirm that your new settings are working as expected, preserve your configuration changes by saving the Running Config file.

## Audit log events

The following events on an ExtraHop appliance generate an entry in the audit log.

Category	Event
Agreements	<ul style="list-style-type: none"> <li>A EULA or POC agreement is agreed to</li> </ul>
API	<ul style="list-style-type: none"> <li>An API key is created</li> <li>An API key is deleted</li> </ul>
Appliance Migration	<ul style="list-style-type: none"> <li>An appliance migration is started</li> <li>An appliance migration succeeded</li> <li>An appliance migration failed</li> </ul>
Appliance user	<ul style="list-style-type: none"> <li>A user is added</li> <li>User metadata is edited</li> <li>A user is deleted</li> <li>A user password is set</li> <li>A user other than the <b>setup</b> user attempts to modify the password of another user</li> <li>A user password is updated</li> </ul>
Atlas	<ul style="list-style-type: none"> <li>The Atlas Remote UI account is enabled</li> </ul>

Category	Event
Browser sessions	<ul style="list-style-type: none"> <li>The Atlas Remote UI account is disabled</li> <li>The connection to the Atlas Service is reset</li> <li>A Discover appliance disconnects from the Atlas Service</li> </ul>
Command appliance	<ul style="list-style-type: none"> <li>A specific browser session is deleted</li> <li>All browser sessions are deleted</li> <li>A Discover appliance connects to a Command appliance</li> <li>A Discover appliance disconnects from a Command appliance</li> <li>An Explore or Trace appliance establishes a tunneled connection to a Command appliance</li> <li>Command appliance information is set</li> <li>A Command nickname is set</li> <li>Enable or disable a Discover appliance</li> <li>The Discover appliance Web UI is remotely viewed</li> <li>A license for a Discover appliance is checked by a Command appliance</li> <li>A license for a Discover appliance is set by a Command appliance</li> </ul>
Dashboards	<ul style="list-style-type: none"> <li>A dashboard is created</li> <li>A dashboard is renamed</li> <li>A dashboard is deleted</li> <li>A dashboard permalink, also known as a short code, is modified</li> <li>Dashboard sharing options are modified</li> </ul>
Datastore	<ul style="list-style-type: none"> <li>The extended datastore configuration is modified</li> <li>The datastore is reset</li> <li>A datastore reset completed</li> <li>Customizations are saved</li> <li>Customizations are restored</li> <li>Customizations are deleted</li> </ul>
Detections	<ul style="list-style-type: none"> <li>A detection is acknowledged</li> <li>A detection acknowledgement is reset</li> <li>A detection rule is added</li> <li>A detection rule description is updated</li> <li>A detection rule is enabled</li> <li>A detection rule is disabled</li> <li>A detection rule is extended</li> </ul>
Exception files	<ul style="list-style-type: none"> <li>An exception file is deleted</li> </ul>
Explore appliance records	<ul style="list-style-type: none"> <li>All Explore appliance records are deleted</li> </ul>

Category	Event
Explore cluster	<ul style="list-style-type: none"> <li>• A new Explore node is initialized</li> <li>• A node is added to an Explore cluster</li> <li>• A node is removed from an Explore cluster</li> <li>• A node joins an Explore cluster</li> <li>• A node leaves an Explore cluster</li> <li>• A Discover or Command appliance is paired to an Explore appliance</li> <li>• A Discover or Command appliance is unpaired from an Explore appliance</li> <li>• An Explore node is removed or missing, but not through a supported interface</li> </ul>
ExtraHop Update Service	<ul style="list-style-type: none"> <li>• A detection category is updated</li> <li>• A detection definition is updated</li> <li>• A detection trigger is updated</li> <li>• A ransomware definition is updated</li> <li>• Detection metadata is updated</li> <li>• Expanded detection content is updated</li> </ul>
Firmware	<ul style="list-style-type: none"> <li>• Firmware is upgraded</li> <li>• Archived firmware is deleted</li> </ul>
License	<ul style="list-style-type: none"> <li>• A new static license is applied</li> <li>• License server connectivity is tested</li> <li>• A product key is registered with the license server</li> <li>• A new license is applied</li> </ul>
Login from Web UI or Admin UI	<ul style="list-style-type: none"> <li>• A login succeeds</li> <li>• A login fails</li> </ul>
Login from SSH or REST API	<ul style="list-style-type: none"> <li>• A login succeeds</li> <li>• A login fails</li> </ul>
Network	<ul style="list-style-type: none"> <li>• A network interface configuration is edited</li> <li>• The hostname or DNS setting is changed</li> <li>• A network interface route is changed</li> </ul>
Offline capture	<ul style="list-style-type: none"> <li>• An offline capture file is loaded</li> </ul>
PCAP	<ul style="list-style-type: none"> <li>• A packet capture (PCAP) file is downloaded</li> </ul>
RPCAP	<ul style="list-style-type: none"> <li>• An RPCAP configuration is added</li> <li>• An RPCAP configuration is deleted</li> </ul>
Running Config	<ul style="list-style-type: none"> <li>• The running configuration file changes</li> </ul>
SAML Identity Provider	<ul style="list-style-type: none"> <li>• An identity provider is added</li> <li>• An identity provider is modified</li> <li>• An identity provider is deleted</li> </ul>

Category	Event
SAML login	<ul style="list-style-type: none"> <li>• A login succeeds</li> <li>• A login fails</li> </ul>
SSL decryption	<ul style="list-style-type: none"> <li>• An SSL decryption key is saved</li> </ul>
SSL session keys	<ul style="list-style-type: none"> <li>• A PCAP session key is downloaded</li> </ul>
Support account	<ul style="list-style-type: none"> <li>• The support account is disabled</li> <li>• The support account is enabled</li> <li>• The support key is regenerated</li> </ul>
Support Script	<ul style="list-style-type: none"> <li>• A default support script is running</li> <li>• A past support script result is deleted</li> <li>• A support script is uploaded</li> </ul>
Syslog	<ul style="list-style-type: none"> <li>• Remote syslog settings are updated</li> </ul>
System and service status	<ul style="list-style-type: none"> <li>• The system starts up</li> <li>• The system shuts down</li> <li>• The system is restarted</li> <li>• The bridge, capture, or portal process is restarted</li> <li>• A system service is enabled (such as SNMP, web shell, management, SSH)</li> <li>• A system service is disabled (such as SNMP, web shell, /management, SSH)</li> </ul>
System time	<ul style="list-style-type: none"> <li>• The system time is set</li> <li>• The system time is changed</li> <li>• The system time is set backwards</li> <li>• NTP servers are set</li> <li>• The time zone is set</li> <li>• A manual NTP synchronization is requested</li> </ul>
Trace appliance	<ul style="list-style-type: none"> <li>• A new Trace appliance is initialized.</li> <li>• A Discover or Command appliance is connected to a Trace appliance.</li> <li>• A Discover or Command appliance is disconnected from a Trace appliance</li> </ul>
Trace appliance packetstore	<ul style="list-style-type: none"> <li>• A Trace appliance packetstore is reset</li> </ul>
Trends	<ul style="list-style-type: none"> <li>• A trend is reset</li> </ul>
Triggers	<ul style="list-style-type: none"> <li>• A trigger is added</li> <li>• A trigger is edited</li> <li>• A trigger is deleted</li> </ul>