

Configure a new Explore cluster with manager nodes

Published: 2022-09-29

A manager node is dedicated to cluster management tasks and does not store records. This guide provides guidelines for adding three manager nodes to new clusters that have six or more data-only nodes.

Before you begin

- Review the specifications and guidelines in [Deploying manager nodes](#).
- Deploy three manager-only nodes and six or more data-only nodes according to the [guide for your implementation](#), but do not join the nodes to form a cluster or connect the nodes to Discover or Command appliances.
- Depending on your implementation, reduce the data disk size to meet the [manager node specifications](#).
- [Register each node](#) with the correct product license. Manager-only nodes have dedicated SKUs; be sure to verify these licenses with your account team. After all nodes are registered, [join the nodes to create a cluster](#).

Create the Explore cluster

Follow the steps in [Create a recordstore cluster](#) to join all of the nodes.

Configure three manager-only nodes

1. Log in to the Administration settings on a node intended for cluster task management.
2. In the Appliance Settings section, click **Running Config**.
3. Click **Edit config**.
4. Add an entry to the Running Config file by completing the following steps:
 - a) Add a comma after the second to last curly brace (}).
 - b) Press ENTER to create a new line.
 - c) Paste the following code on the new line before the final curly brace:

```
"cluster": {  
    "data": false,  
    "min_master_nodes": 2  
}
```

5. Click **Update**.
6. Click **Done**.
7. Click **Save config** and then click **Save**.
8. In the Appliance Settings section, click **Shutdown or Restart**.
9. Next to the Search service, click **Restart**.
10. Repeat these steps on each manager-only node.

Configure the data-only nodes

1. Log in to the Administration settings on a node intended for data storage.
2. In the Appliance Settings section, click **Running Config**.

3. Click **Edit config**.
4. Add an entry to the Running Config file by completing the following steps:
 - a) Add a comma after the second to last curly brace (}).
 - b) Press ENTER to create a new line.
 - c) Paste the following code on the new line before the final curly brace:

```
"cluster": {  
    "master": false,  
    "min_master_nodes": 2  
}
```

5. Click **Update**.
6. Click **Done**.
7. Click **Save config** and then click **Save**.
8. In the Appliance Settings section, click **Shutdown or Restart**.
9. Next to the Search service, click **Restart**.
10. Repeat these steps on each data-only node.

Next steps

After all of the nodes are configured with their designated role, [connect each data-only node to Discover and Command appliances](#). Manager nodes should not be connected to a Discover or Command appliance.



Tip: [Learn how to add or remove nodes from a cluster that has manager nodes](#).