

# Monitor network segmentation with custom detections

Published: 2024-03-27

Segmenting your network into discrete subnetworks can help improve security by only allowing certain clients to access servers that contain sensitive data. By creating a custom detection, you can identify when a machine outside of a privileged subnetwork communicates with a device inside of the subnetwork, so you can ensure that your security conventions are being enforced.

In this walkthrough, we'll create a device group for our privileged subnetwork and write a trigger that creates a detection every time an outside machine contacts the group.

## Create a device group for the privileged subnetwork

First, we'll create a device group that contains all IP addresses in the following CIDR blocks:

- 192.168.1.0/24
- 192.168.2.0/24



**Note:** You can modify these CIDR blocks to match a specific subnetwork in your environment.

1. Log in to the ExtraHop system through `https://<extrahop-hostname-or-IP-address>`.
2. Click **Assets**.
3. Click **Device Groups**.
4. Click **Create Device Group**.
5. In the Group Name text box, type `Privileged Network`.
6. Click **Dynamic**.
7. Click **Match All** and then select **Match Any** from the drop-down menu.
8. Click **Name**, and then select **IP Address** from the drop-down menu.
9. In the text box, type `192.168.1.0/24`.
10. Click **Add Filter** to add an additional filter.
11. Click **Name**, and then select **IP Address** from the drop-down menu.
12. In the text box, type `192.168.2.0/24`.


## Create a trigger to generate custom detections

Next, we will create the trigger that generates custom detections. Triggers generate custom detections by calling the `commitDetection` function in the trigger script.

The trigger identifies traffic from outside the privileged subnetwork by checking the `hasTrigger` property of the client device for each flow. The `hasTrigger` property indicates whether the trigger is running on the device. Because the trigger is assigned to all devices in the Privileged Network device group, the `hasTrigger` property will be false for all devices outside of the subnetwork.



**Note:** For more information about the `commitDetection` function, see the [Trigger API Reference](#).

1. Click the System Settings icon  and then click **Triggers**.
2. Click **Create**.
3. In the Name field, type `Network Segmentation Custom Detection`.

- In the Description field, type the following text:

```
Creates a detection every time a device in the privileged network communicates with a device outside of the privileged network.
```


- Click in the Events field and select **FLOW\_CLASSIFY**.  
The trigger runs on the FLOW\_CLASSIFY event, which runs as a flow is initially associated with a specific protocol. This step ensures that all flows are investigated for suspicious behavior.
- In the Assignments field, type `Privileged Network`, and then select the group you created in the previous procedure.
- In the right pane, type the following trigger script:

```
const client = Flow.client.device;
const server = Flow.server.device;
if (!client.hasTrigger) {
  commitDetection('network_segmentation_breach', {
    title: 'Network Segmentation Breach',
    description: `Device ${client.id} accessed privileged device
    ${server.id} over ${Flow.l7proto}`,
    categories: ['sec.caution'],
    riskScore: 80,
    participants: [{
      object: client,
      role: 'offender'
    }, {
      object: server,
      role: 'victim'
    }],
    identityKey: [client.id, server.id].join('!!!'),
  });
}
```

- Click **Save** and then click **Done**.

## Create a custom detection type

Next, we will create a custom detection type, which enables you to add display names and MITRE categories to custom detections.

- Click the System Settings icon  and then click **Detection Catalog**.
- Click **Create**.
- In the Display Name field, type `Network Segmentation Breach`.
- In the Detection Type ID field, type `network_segmentation_breach`.
- Click **Save**.

## View custom detections

After you save the trigger, you can view detections the trigger generates on the Detections page.

- Click **Detections**.
- Click **Types**.
- Click **Network Segmentation Breach** to view details about each individual detection.



**Note:** **Network Segmentation Breach** only appears if detections are generated by the trigger during the selected time interval.

Next steps

- Generate alerts for the detection by [configuring detection alert settings](#). For example, you can configure your ExtraHop system to email you when a detection occurs.